

## **Product Information**

## CT 325 Double-Sided PVC Film "Bag Closing" Tape

## **Description:**

Double-sided adhesive PVC film tape without a liner. The adhesive on both sides is balanced, so it can be unwound easily, even after long periods in storage.

## **Application:**

- Especially suited as closure system even for thin film bags.
- Mounting light weight parts.
- Splicing of various materials such as plastic, metal foils, paper, and cardboards.

Technical Data	
Adhesive	Acrylic
Substrate	PVC Film
Thickness (mils)	3.38 (0.09 mm)
Adhesion to Steel (oz/in of width)	27.4 (7.49 N/25mm)
Tensile Strength (lbs/in of width)	19.98 (89.4 N/25mm)
Elongation (% at Break)	30
Temperature Resistance (Short Term)	158°F (70°C)
Temperature Resistance (Long Term)	140°F (60°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.