

CT #627

HVAC and Insulation Foil Tape

627 is a 1.6 mil, aluminum foil tape with an aggressive acrylic adhesive system and a 60 pound silicone coated Kraft liner. The solvent acrylic adhesive bonds tightly and permanently to insulation facing and HVAC ducts. This is a UL Listed tape under UL File #R26374.

Application:

- Bonds tightly and permanently to insulation facing and HVAC ducts
- Performs well over a wide range of environmental conditions

TECHNICAL DATA

Adhesive	Solvent Acrylic
Substrate	Aluminum Foil
Thickness	3.1 Mils (0.0787 mm)
Adhesion to Steel	60 oz/in (6.6 N/cm)
Tensile Strength	20 lbs/in (35 N/cm)
Elongation (% at Break)	3
Minimum Service Temp.	-25°F (-32°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St PL SE, Hickory, NC 28602 Phone: 800-237-6079 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.