

Printed Metalized Polycoated

waterproof polycoated cloth duct tape

Meets Specs: UL 723, Flame Spread Index-15, Smoke Development Index-30.

Designed specifically for HVAC industry for use on Class I flexible

duct installations

683 is a printed, metalized, and

with a natural rubber adhesive.

CT #683

Application:

Cloth Duct Tape

TECHNICAL DATA

| Adhesive | Natural Rubber |
|----------------------------|--------------------------------|
| Substrate | Waterproof Polycoated Cloth |
| Thickness | 10 Mils (0.25 mm) |
| Adhesion to Steel | 55 oz/in (6.02 N/10mm) |
| Tensile Strength | 25 lbs/in (43.8 N/10mm) |
| Elongation (% at Break) | 18 |
| Service Temp. Min | 50°F (10°C) |
| Service Temp. Max | 200°F (93°C) |

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St PL SE, Hickory, NC 28602 Phone: 800-237-6079 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.