

## TECHNICAL DATA

## Adhesive Acrylic Single-Coated Substrate Closed Cell PVC Foam Thickness 60 Mils (1.524 mm) Tensile 30 lbs/in Strength Elongation 150 (% at Break) -40°F to 180°F Service **Temperature** (-40°C to 82°C) Application 50°F to 110°F (10°C to 45°C) Temperature

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

CT #820

## Natural Cork UV Resistant PVC Foam Tape

820 is a 1/16" thick, UV resistant, 8 lb density, single-coated closed cell PVC foam tape with an acrylic adhesive that offers long service life. It is also available in 1/8" thick (#821), 3/16" thick (#822), 1/4" thick (#823), 3/8" thick (#824), and 1/2" thick (#825).

## Application:

- Used for gasketing, weather stripping, sound deadening, and shock absorption
- Seals out air, moisture, light, and dust when compressed at least 30%
- Offers long service life

Carolina Tape & Supply Corporation 502 19<sup>th</sup> St PL SE, Hickory, NC 28602 Phone: 800-237-6079 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.