



Product Information

CT #416

PCB Masking Tape

416 is a 1 mil polyester film tape with a 3 mil silicone, red adhesive.

Application:

- Stop-off applications in the production of printed circuit boards
- Particularly for use in tin/lead stripping
- "Gold finger" plating operations
- Silicone splicing

TECHNICAL DATA

Adhesive	Silicone
Substrate	Polyester Film

Thickness	4 Mils (0.102 mm)
------------------	----------------------

Adhesion to Steel	25 oz/in (6.8 N/25mm)
--------------------------	--------------------------

Tensile Strength	23 lbs/in (101 N/25mm)
-------------------------	---------------------------

Elongation (% at Break)	100
-----------------------------------	-----

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.