



Product Information

CT #404

Premium Plastic Vinyl Electrical Tape

404 is a premium grade, 7 mil, plastic vinyl electrical tape suitable for all weather conditions and flame retardant.

Meets Specs: UL 510, CSA 22.2; ASTM-D-3005; HH-I-595C.

Application:

- Quick identification and color coding of electrical circuits, containers, or conduit systems
- Primary insulation of not more than 600 volts

TECHNICAL DATA

Substrate	Plastic Vinyl
------------------	---------------

Thickness	7 Mils (0.178 mm)
------------------	----------------------

Adhesion to Steel	20 oz/in (2.2 N/cm)
--------------------------	------------------------

Tensile Strength	17 lbs/in (30 N/cm)
-------------------------	------------------------

Elongation (% at Break)	260
-----------------------------------	-----

Temperature Rating Min	UL: 14°F (-10°C) CSA: -0.4°F (-18°C)
-------------------------------	---

Temperature Rating Max	UL: 176°F (80°C) CSA: 221°F (105°C)
-------------------------------	--

Dielectric Strength	9,000 Volts 8,100 Volts (wet)
----------------------------	----------------------------------

Insulation Resistance	1x10 ⁶ MΩ
------------------------------	----------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.