



Product Information

CT 106 Medium Temp, Medium Grade Paper Masking Tape

Description:

A beige, high temperature, medium crepe, paper masking tape with pressure-sensitive natural rubber adhesive. Can withstand exposure to forced drying conditions up to 250°F (121°C) for 30 minutes with warm to hot removal recommended. Excellent quick-stick properties. Designed for applications requiring transfer resistance in conjunction with a variety of paints and surfaces. Special release coat provides an extra measure of moisture and solvent resistance. Not recommended for outdoor exposure.

Application:

- Interior paint masking; spray painting (air-dry) autos, boats, etc.
- Boat manufacturing (fiberglass), silk screening, mail rooms, and marble manufacturing (man-made).
- Golf club shaft (build-up), carpet pad/pad splicing, and freezer tape.
- Light bundling, packaging, splicing, and tabbing.

Technical Data

Adhesive	Natural Rubber/Resin
Substrate	Medium Crepe Paper
Thickness (mils)	6.4 (0.162 mm)
Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
Tensile Strength (lbs/in of width)	26 (114 N/25mm)
Elongation (% at Break)	9
Service Temperature	40°F to 250°F (4.4°C to 121°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.