

Product Information

CT 110 Multi-Surface, 14-Day Painter's Tape

Description:

Premium grade, medium adhesion blue painter's tape for interior and exterior masking of multiple surfaces, such as painted walls, glass, vinyl, metal, and wood, when easy, no-residue removal is a must. Designed with a synthetic rubber-based adhesive that prevents lifting and paint seepage, while allowing it to remove cleanly from surfaces without damage for up to 14 days.

Application:

- For interior and exterior use on multiple surfaces, including painted walls, glass, vinyl,
- Not recommended for use on wallpaper, unpainted wallboard, ceiling tile, or with uncured

	Technical Data
Adhesive	Synthetic Rubber-Based
Substrate	Crepe Paper
Thickness (mils)	5.6 (0.14 mm)
Adhesion to Steel (oz/in of width)	32 (3.5 N/10mm)
Tensile Strength (lbs/in of width)	27 (47.3 N/10mm)
Elongation (% at Break)	8
Service Temperature	50°F to 200°F (10°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.