

Product Information

CT 120 30 Day UV-Resistant Premium Paper Masking Tape

Description:

An aluminized, silver, saturated crepe paper backing protects the specially formulated, high temperature resistant, pressure-sensitive natural rubber adhesive from the effects of UV light. Can be used in outdoor applications for periods of up to one month depending on the weather conditions and the surface to which the tape is applied.

Application:

• Windshield repair/replacement for automotive, truck, bus, and marine.

,	Technical Data
Adhesive	Natural Rubber/Resin
Substrate	Aluminized Crepe Paper
Thickness (mils)	6.8 (0.17 mm)
Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
Tensile Strength (Ibs/in of width)	22 (96 N/25mm)
Elongation (% at Break)	8
Service Temperature	50°F to 325°F (10°C to 163°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602 Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.