

## **Product Information**

## CT 201 Tan Medium Grade Paper Flatback Tape

## **Description:**

A quick, sure sealing, economical, pressure-sensitive flatback tape which can increase packaging line efficiency. Offers a positive attractive seal and excellent adhesion to discourage pilfering. Performs well under a wide range of temperatures through a wide range of humidity conditions. Offers the advantages of a balance of high quick stick and excellent holding properties. Performs well as a low temperature splicing tape and meets USPS requirements. Product is not repulpable.

## **Application:**

• Can be used on all cartons.

Government Compliance: ASTM D6123, Type II; PPP-T-42C, Type II; C.I.D A-A-883B Type II; Boeing BAC 5317

	Technical Data
Adhesive	Natural Rubber/Resin
Substrate	Kraft Flatback
Thickness (mils)	6 (0.15 mm)
Adhesion to Steel (oz/in of width)	57 (15.6 N/25mm)
Tensile Strength (lbs/in of width)	36 (157.6 N/25mm)
Elongation (% at Break)	3
Service Temperature	40°F to 225°F (4°C to 107°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.