



Product Information

CT 202 Premium Grade Bleached Flatback Paper Tape

Description:

Packaging premium grade flatback paper tape for splicing and hand and machine carton sealing applications, and general purpose applications where a thick paper tape is necessary. Constructed with a heavy duty kraft backing coated with a high-tack rubber-based adhesive, giving it extra strength, in addition to abrasion, water, solvent, and oil resistance.

Application:

- For splicing various substrates.
- Also used for heavy duty hand and machine carton sealing applications.
- Also used for general purpose applications where a thick, flatback paper tape is required.
- Meets or exceeds requirements for motor freight, railway, air express, air freight, postal shipments, and government packaging when used as a carton sealing tape.

Meets Standards: ASTM D 6123/D 6123M-97 (2012), Type II; ASTM D 5486M-12, Type V

Technical Data

Adhesive	Natural Rubber/Resin
Substrate	Kraft Flatback
Thickness (mils)	6 (0.15 mm)
Adhesion to Steel (oz/in of width)	57 (15.6 N/25mm)
Tensile Strength (lbs/in of width)	36 (157.6 N/25mm)
Elongation (% at Break)	3
Service Temperature	40°F to 225°F (4°C to 107°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.