



Product Information

CT 311 Double-Coated Crepe Paper Tape

Description:

Impregnated crepe paper coated on both sides with a rubber-based adhesive. The adhesive exhibits high tack and moderate shear properties. Crepe substrate offers strength, conformability, and stability for die cutting. Carrier also provides hand tear ability.

Application:

- For bonding and laminating to a wide variety of plastics, metals, papers, also various types of parts to be machined.
- Also used for splicing applications and core start-up applications.
- General purpose product, used in golf grip applications.

Technical Data

<i>Adhesive</i>		Rubber-Based
<i>Substrate</i>		Crepe Paper
<i>Liner</i>		60# White Densified Kraft
<i>Thickness (mils)</i>		6.0 (0.15 mm)
<i>Adhesion to Steel (oz/in of width)</i>	Exposed Side	100 (27.3 N/25mm)
	Liner Side	85 (23.2 N/25mm)
<i>Service Temperature</i>		30°F to 150°F (-1.1°C to 65.6°C)
<i>Application Temperature</i>		68°F to 100°F (15.6°C to 37.8°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.