

Product Information

CT 316 7.0 Mil Premium Double-Coated Flatback Tape

Description:

Bleached flatback paper product coated with a high shear resistant pressure-sensitive natural rubber/resin adhesive on both sides that bond equally well to almost any surface. White colored easy release treated crepe paper liner allows for either machine or hand application. A recognized standard in the manufacture and repair of golf club grip application.

Application:

- Golf club manufacture and golf grip replacement and repair.
- Photograph mounting, carpet installation, textile manufacturing ("twister room"), steel-rule die (make-ready), and any application that requires two adhesive surfaces for joining.

Technical Data		
Adhesive		Natural Rubber/Resin
Substrate		Bleached Flatback
Thickness (mils)	With Liner	12 (0.3 mm)
	Without Liner	7 (0.178 mm)
Adhesion to Steel (ozs/in of width)		52 (14.2 N/25mm)
Quick Stick to Steel (oz/in of width)		20 (5.5 N/25mm)
Tensile Strength (Ibs/in of width)		34 (149 N/25mm)
Elongation (% at Break)		3
Temperature Resistance (Max.)		200°F (93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.