



Product Information

CT 321 Double-Coated Crepe Paper Tape

Description:

3.5 mil impregnated crepe paper coated on both sides with a synthetic-based adhesive. The adhesive exhibits ultra high tack and moderate shear properties.

Economical, general purpose double-coated tape designed for applications where good tensile strength is needed.

Application:

- For use in parts matching, where removal of tape is essential.
- Core start-up.

Technical Data

<i>Adhesive</i>		Synthetic-Based
<i>Substrate</i>		Crepe Paper
<i>Liner</i>		60# Silicone Treated Paper
<i>Thickness (mils)</i>		6.0 (0.15 mm)
<i>Adhesion to Steel (oz/in of width)</i>	Exposed Side	80 (21.9 N/25mm)
	Liner Side	80 (21.9 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>		16 (71.6 N/25mm)
<i>Elongation (% at Break)</i>		5
<i>Shear Strength (250 gm/in² @ 72°F)</i>		6+ Days
<i>Service Temperature</i>		30°F to 150°F (-1.1°C to 65.6°C)
<i>Application Temperature</i>		68°F to 100°F (20°C to 37.8°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.