



Product Information

CT 358

Double-Coated Gasketing Adhesive Tape

Description:

Double-coated tissue with an extremely aggressive acrylic adhesive. Supplied with a 60# Kraft release liner. Offers exceptionally high tack and peel while the tissue carrier adds strength and dimensional stability. Bonds well to low surface energy substrates.

Application:

- Foam gasketing and sound attenuation
- Bonds EPDM rubber and some plastic materials
- Foam fabrication
- Difficult splicing applications

Technical Data

Adhesive	Acrylic
Substrate	Tissue
Thickness (mils)	4.1 (0.104 mm)
Adhesion to Steel (oz/in of width)	104 (29 N/25mm)
Application Temperature	65°F (18°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.