



Product Information

CT 362

Double-Coated Polyethylene Foam Tape

Description:

1/8" thick polyethylene foam tape with a high performance acrylic adhesive. Available in different thicknesses.

Application:

- Glazing tape
- Sound attenuation and vibration dampening
- Gasketing
- Decorative trim

Technical Data

Adhesive	Acrylic
Substrate	Polyethylene
Thickness	1/8"
Adhesion to Steel (oz/in of width)	128 (14 N/10mm)
Tensile Strength (lbs/in of width)	180 (1,241 kPa)
Elongation (% at break)	295
Service Temperature	-40°F to 180°F (-40°C to 82.2°C)
Application Temperature	40°F to 100°F (4.4°C to 37.8°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.