



Product Information

CT 701 Lithographic Red Tape

Description:

Red cellophane lithographic tape with a natural rubber adhesive coated on one side. Special design for sight transparency to facilitate easy positioning of the tape and the negative film in processing lithographic plates, while masking UV light. Anti-static, hand tearable, and repositionable.

Application:

- Negative film masking in processing lithographic printing plates.
- Carton sealing, film splicing, stationery.

Technical Data

<i>Adhesive</i>	Natural Rubber (Solvent Based)
<i>Substrate</i>	Transparent Cellophane
<i>Thickness (mils)</i>	2.3 (0.58 mm)
<i>Adhesion to Steel (oz/in of width)</i>	27 (7.38 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	17 (76.05 N/25mm)
<i>Elongation (% at Break)</i>	20
<i>Service Temperature</i>	50°F to 212°F (10°C to 100°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.