



Product Information

CT #609

All Temperature Laminated FSK

609 is a laminated foil/scrim/kraft tape with a high tack and all weather synthetic rubber adhesive and a paper release line. This tape offers a permanent bond and resists water vapor and smoke transmission.

Meets Specs: UL 723; Flame Spread Index-10, Smoke Development Index-10; US Green Building Council - LEED® Point contributor product.

Application:

- Sealing, seaming, and joining scrim-reinforced pipe and duct insulation in all weather conditions
- Resists water vapor and smoke transmissions

TECHNICAL DATA

Adhesive	All Weather Synthetic Rubber
-----------------	------------------------------

Substrate	Laminated FSK
------------------	---------------

Thickness (With Liner)	9.4 Mils (0.24 mm)
-------------------------------	--------------------

Thickness (Without Liner)	6.6 Mils (0.17 mm)
----------------------------------	--------------------

Adhesion to Steel	60 oz/in (6.57 N/10mm)
--------------------------	------------------------

Tensile Strength	40 lbs/in (70.1 N/10mm)
-------------------------	-------------------------

Elongation (% at Break)	1
--------------------------------	---

Application Temperature	32°F to 230°F (0°C to 110°C)
--------------------------------	------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.