



## Product Information

### CT #610

### Metalized Polycoated Cloth Duct Tape

610 is a metalized polycoated cloth duct tape with a natural rubber adhesive.

Meets Spec: UL 723, Flame Spread Index-5, Smoke Development Index-15.

#### Application:

- HVAC use on flex duct, sheet metal, rigid duct board, air vents, insulations, and fibrous filter banks and air pollution systems
- Variety of industrial uses

#### TECHNICAL DATA

<b>Adhesive</b>	Natural Rubber
<b>Substrate</b>	Metalized Polycoated Cloth
<b>Thickness</b>	10 Mils (0.25 mm)
<b>Adhesion to Steel</b>	55 oz/in (6.02 N/10mm)
<b>Tensile Strength</b>	25 lbs/in (43.8 N/10mm)
<b>Elongation</b> (% at Break)	18
<b>Service Temp. Min</b>	50°F (10°C)
<b>Service Temp. Max</b>	200°F (93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.