



Product Information

CT #620

Quality Grade Polycoated Cloth Duct Tape

620 is a quality grade, polycoated cloth duct tape with a high tack, natural rubber adhesive.

Meets Spec: UL 723, Flame Spread Index-5, Smoke Development Index-25.

Application:

- Indoor/outdoor applications in industrial, HVAC, utilities, trucking, and automotive applications
- Used to repair, seam, hold, protect, mask, create moisture barrier, bundle, and splice

TECHNICAL DATA

Adhesive	Natural Rubber
Substrate	Polycoated Cloth

Thickness	11 Mills (0.28 mm)
------------------	-----------------------

Adhesion to Steel	62 oz/in (6.79 N/10mm)
--------------------------	---------------------------

Tensile Strength	27 lbs/in (47.3 N/10mm)
-------------------------	----------------------------

Elongation (% at Break)	10
-----------------------------------	----

Service Temp. Min	50°F (10°C)
--------------------------	-------------

Service Temp. Max	200°F (93°C)
--------------------------	--------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.