



Product Information

CT #412

Abrasion Resistant Polyester Film Tape

412 is a 2 mil polyester film with a thermosetting rubber adhesive and is non-corrosive. The tape is resistant to abrasion and available in clear and yellow colors. This tape has a temperature performance up to 130°C.

Meets Spec: MIL-I-15126F, Type MFT.

Application:

- Tough, abrasion resistant tape used for a variety of electrical applications requiring temperature performance up to 130°C

TECHNICAL DATA

Adhesive	Thermosetting Rubber
-----------------	----------------------

Substrate	Polyester Film
------------------	----------------

Thickness	3.5 Mils (0.09 mm)
------------------	-----------------------

Adhesion to Steel	45 oz/in (12.3 N/25mm)
--------------------------	---------------------------

Tensile Strength	50 lbs/in (219 N/25mm)
-------------------------	---------------------------

Elongation (% at Break)	100
--------------------------------	-----

Dielectric Strength	5,000 Volts
----------------------------	-------------

Insulation Class	130°C
-------------------------	-------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.