



Product Information

CT #958

Lead Foil Tape

958 is a 5 mil lead foil tape with an aggressive, solvent resistant, rubber-based adhesive and 3 mil release liner.

Meets Specs: HH-T-29A; AMDT 2.

Application:

- Used extensively for decorative, leaded windows
- Vapor barrier
- Radiation/x-ray shielding and as masking for electroplating
- Very conformable

TECHNICAL DATA

Adhesive	Rubber-Based
-----------------	--------------

Substrate	Lead Foil
------------------	-----------

Thickness	5 Mils (0.127 mm)
------------------	----------------------

Adhesion to Steel	90 oz/in (7.9 N/cm)
--------------------------	------------------------

Tensile Strength	21.5 lbs/in (37.7 N/cm)
-------------------------	----------------------------

Elongation (% at Break)	5
-----------------------------------	---

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.