



## Product Information

### CT #771

### Protective Overlay Polyethylene Film Tape

771 is a black polyethylene film with an acrylic adhesive with high elongation (clear available – 10 case minimum).

#### Application:

- High elongation tape for protective overlay of surfaces requiring resistance to solvents and chemicals

#### TECHNICAL DATA

<b>Adhesive</b>	Acrylic
<b>Substrate</b>	Black or Clear Polyethylene Film
<b>Thickness</b>	8 Mils (0.203 mm)
<b>Adhesion to Steel</b>	45 oz/in 4.92 N/cm
<b>Tensile Strength</b>	18 lbs/in (31.52 N/cm)
<b>Elongation</b> (% at Break)	600%
<b>Operating Temperature</b>	-40°F to 190°F (-40°C to 88°C)
<b>Application Temperature</b>	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.