



Product Information

CT #726

Warning Stripe Film Tape

726 is a general purpose grade, 1.1 mil, and clear Vylon reinforced film tape with a synthetic rubber blend adhesive.

Meets Specs: PPP-T-70A; CID-A-A-1684A.

Application:

- Various closure applications
- Excellent performance in wide temperature range: from 0°F to 200°F

TECHNICAL DATA

| | |
|-----------------|------------------------|
| Adhesive | Synthetic Rubber Blend |
|-----------------|------------------------|

| | |
|------------------|-----------------------------|
| Substrate | Clear Vylon Reinforced Film |
|------------------|-----------------------------|

| | |
|------------------|--------|
| Thickness | 2 Mils |
|------------------|--------|

| | |
|--------------------------|----------|
| Adhesion to Steel | 20 oz/in |
|--------------------------|----------|

| | |
|-------------------------|-----------|
| Tensile Strength | 20 lbs/in |
|-------------------------|-----------|

| | |
|-----------------------------------|-----|
| Elongation (% at Break) | 160 |
|-----------------------------------|-----|

| | |
|------------------------------|-------------------------------------|
| Operating Temperature | -60°F to 200°F (-51°C to 93.3°C) |
|------------------------------|-------------------------------------|

| | |
|--------------------------------|----------------------------------|
| Application Temperature | 32°F to 150°F (0°C to 65.6°C) |
|--------------------------------|----------------------------------|

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.