



Product Information

CT #729

High Performance Grade Vylon Film Tape

729 is a high performance grade film tape with a 4 mil, clear Vylon film backing and a high grade emulsion acrylic adhesive. This tape offers excellent resistance and a wide operating temperature range.

Application:

- Packaging, laminating, edging, hinging, label protection, tabbing, and splicing
- Excellent for separating dissimilar metals to prevent electrolytic corrosion
- Resistance to moisture, aging, weathering, sunlight, chemicals, oils, and acids
- Wide temperature range

TECHNICAL DATA

Adhesive	Emulsion Acrylic
-----------------	------------------

Substrate	Clear Vylon Film
------------------	------------------

Thickness	5 Mils
------------------	--------

Adhesion to Steel	35 oz/in
--------------------------	----------

Tensile Strength	180 lbs/in
-------------------------	------------

Elongation (% at Break)	35
-----------------------------------	----

Operating Temperature	-30°F to 200°F (-34°C to 93.3°C)
------------------------------	-------------------------------------

Application Temperature	32°F to 150°F (0°C to 65.6°C)
--------------------------------	----------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.