



Product Information

CT #794

Super Tack Seaming and Bonding Film Tape

794 is a polyester film tape with a rubber-resin adhesive for adhering to polyesters, polyethylenes, and many other difficult-to-adhere-to surfaces. While the polyester backing offers abrasion, chemical, and thermal resistance; the aggressive adhesion offers immediate adhesion for easy application and adheres to difficult-to-stick-to surfaces.

Application:

- Splicing, sealing, repairing, holding, and reinforcing a variety of difficult-to-hold materials
- Repairing and reinforcing high-wear areas of rip-stop nylon
- Holding polyethylene barrel liners in place
- Splicing large photographic acetate transparencies

TECHNICAL DATA

Adhesive	Rubber-Resin
-----------------	--------------

Substrate	Polyester
------------------	-----------

Thickness	4.1 Mils (0.10 mm)
------------------	-----------------------

Adhesion to Steel	140 oz/in
--------------------------	-----------

Tensile Strength	43 lbs/in
-------------------------	-----------

Elongation (% at Break)	140
-----------------------------------	-----

Temperature Range	40°F to 200°F (4°C to 93°C)
--------------------------	--------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.