



Product Information

CT #870

Low Density Open Cell Polyether PU Foam Tape

870 is a low density, open cell polyether and polyurethane foam tape with a high tack synthetic rubber adhesive. The high tack permanent PSA exhibits a superior balance of tack, peel, and holding power on a wide variety of surfaces. It is cost-effective, resists water and moisture, and remains flexible over a long period of demanding usage.

Application:

- Low density and high flexibility allows it to recover quickly
- Good insulating properties
- Automotive and RV door gasketing

TECHNICAL DATA

Adhesive	Synthetic Rubber
-----------------	------------------

Substrate	Polyether PU Foam
------------------	-------------------

Thickness	1000 Mils (25.4 mm)
------------------	------------------------

Tensile Strength	12 to 15 lbs/in
-------------------------	-----------------

Elongation (% at Break)	140
-----------------------------------	-----

Service Temperature	0°F to 140°F (-17.8°C to 60°C)
----------------------------	-----------------------------------

Application Temperature	50°F to 80°F (10°C to 26.7°C)
--------------------------------	----------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.