



Product Information

CT #880

Open Cell Sponge Rubber Tape

880 is a 3/16" thick, open cell sponge rubber tape that features a pressure sensitive acrylic adhesive on one side with a release liner for easy applications. This tape offers a long service life in a wide variety of applications, high compression with a fast recovery, and superior thermal and non-skid properties. It is also available in 5/16" thick (#881).

Application:

- Weather stripping, sound dampening, and shock absorption
- Provides a tight, long-lasting seal against moisture and dust and air leaks
- Weatherproofing doors and windows, and in automobiles and marine uses

TECHNICAL DATA

Adhesive	Acrylic PSA
Substrate	Open Cell Sponge Rubber
Thickness	187.5 Mils (4.76 mm)
Adhesion to Steel	96 oz/in (6 lbs/in)
Application Temperature	50°F to 80°F (10°C to 26.7°C)
Functional Temperature	0°F to 200°F (-17.8°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.