



Product Information

CT 103 Premium Grade, High Adhesion Masking Tape

Description:

Premium grade, natural colored crepe paper with a high adhesion (rubber-based), easy unwind, good quick stick, and adequate conformity, high tensile strength, and resistance to water, solvents, and oils

Product Features:

- High adhesion
- Easy to unwind
- Good quick-stick
- Conformable
- High tensile strength
- Resistant to water, solvents, and oil

Application:

- For industrial and automotive paint applications that do not require the use of a bake oven.
- Can also be used for general purpose masking applications that demand a premium performance tape.

Applicable Standard: ASTM 6123/D 6123M-97 (2012), Type 1

Technical Data

Adhesive	Rubber-Based
Substrate	Smooth Crepe Paper
Thickness (mils)	6.4 (0.16 mm)
Adhesion to Steel (oz/in of width)	39 (4.27 N/10mm)
Tensile Strength (lbs/in of width)	24 (42.0 N/10mm)
Elongation (% at Break)	9
Service Temperature	50°F to 200°F (10°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.