



Product Information

CT 107 High Performance Grade, Med. Temp. Masking Tape

Description:

High performance grade, medium-high adhesion masking tape designed for demanding applications in the transportation, marine, and metal fabrication industries, as well as for wet sanding. Features a rubber-based adhesive and solvent/moisture resistant crepe paper backing that resists paint bleed-through. Can be used in temperatures up to 225°F and removes cleanly.

Application:

- For use in moderate temperature, demanding paint masking applications in the transportation (auto, coaches, buses, and marine), and metal fabrication industries.
- Also used for wet sanding applications.
- Recommended for indoor use only.

Meets Standard: ASTM D 6123/D 6123M-97 (2012), Type 1

Technical Data

Adhesive	Rubber-Based
Substrate	Smooth Crepe Paper
Thickness (mils)	6.9 (0.18 mm)
Adhesion to Steel (oz/in of width)	37 (4.05 N/10mm)
Tensile Strength (lbs/in of width)	31 (54.3 N/10mm)
Elongation (% at Break)	10
Service Temperature	32°F to 225°F (0°C to 107°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.