



Product Information

CT 128 Medium Grade Masking Tape

Description:

Provides an excellent blend of value and performance due to its excellent paper strength, cured rubber adhesive, and high shear. Performs under stress and temperatures where general purpose products fail. Excellent wet grab and should be used when general purpose masking tapes do not perform adequately.

Application:

- Medium temperature masking applications.
- Medium-duty bundling, holding, packaging, and splicing.

Technical Data

<i>Adhesive</i>	Natural Rubber
<i>Substrate</i>	Slightly-Creped Paper
<i>Thickness (mils)</i>	5.8 (0.147 mm)
<i>Adhesion to Steel (oz/in of width)</i>	33.8 (3.7 N/cm)
<i>Tensile Strength (lbs/in of width)</i>	21 (36.8 N/cm)
<i>Elongation (% at Break)</i>	10
<i>Service Temperature</i>	Up to 203°F (95°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.