



Product Information

CT 152 Heavyweight Paper Application Tape

Description:

Standard weight saturated white paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics. Removes easily following graphics application. If adhesive touches adhesive, tape pulls apart easily with no adhesive delamination. Works well in either wet or dry applications with no adhesive transfer.

Application:

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

Technical Data

Adhesive	Rubber-Based
Substrate	Saturated Crepe Paper
Thickness (mils)	5.0 to 5.5 (0.127 to 0.14mm)
Adhesion to Steel (oz/in of width)	16 to 18 (1.8 to 2.0 N/10mm)
Tensile Strength (lbs/in of width)	17 (29.7 N/10mm)
Elongation (% at Break)	3 to 4

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.