



Product Information

CT 177 Industrial Grade, Med-High Adhesion Masking Tape

Description:

Industrial grade, medium-high adhesion masking tape for non-critical painting and industrial applications that demand good adhesion, quick stick, and clean removal. Designed with a synthetic rubber adhesive; conforms to a variety of surfaces, including vinyl, glass, plastic, and rubber without tearing or lifting; and can be used in temperatures up to 150°F (66°C).

Application:

- For non-critical painting and industrial applications that demand good adhesion, quick stick, and clean removal.
- Also used for general purpose packaging, bundling, holding, splicing, and tabbing.
- For use on vinyl, glass, plastic, and rubber.

Meets standards: ASTM D 6123/D 6123M-97 (2012), Type 1

Technical Data	
Adhesive	Synthetic Rubber-Based
Substrate	Crepe Paper
Thickness (mils)	4.9 (0.12 mm)
Adhesion to Steel (oz/in of width)	32 (3.5 N/10mm)
Tensile Strength (lbs/in of width)	19 (33.3 N/10mm)
Elongation (% at Break)	9
Service Temperature	50°F to 150°F (10°C to 66°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.