



Product Information

CT 239 Kraft Medium Grade Paper Flatback Tape

Description:

Aggressive pressure sensitive flatback with an adhesive that has been specifically designed to offer a strong secure seal on a variety of substrates. Moisture resistant and performs well under a wide range of temperatures and humidity conditions. Product is not repulpable.

Application:

- Packaging, carton sealing, splicing, tabbing, and beaming/leasing.
- Silk screening and picture framing.

Government Compliance: PPP-T-42C, Type II; C.I.D. A-A-883, Type II; C.I.D. A-A-1683B; Complies with Postal Regulation for Uninsured Packages

Technical Data

<i>Adhesive</i>	Solvent Cast Natural/Synthetic Rubber
<i>Substrate</i>	Kraft Flatback
<i>Thickness (mils)</i>	7.3 (0.18 mm)
<i>Adhesion to Steel (oz/in of width)</i>	58 (15.9 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	40 (175 N/25mm)
<i>Elongation (% at Break)</i>	7
<i>Service Temperature</i>	40°F to 175°F (4.4°C to 79°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.