



Product Information

CT 306 Double-Coated Polyester Film

Description:

The exposed side adhesive is a general purpose rubber-based adhesive designed for bonding to a wide variety of polyurethane foams, felt, rubber, sponge, cork, abrasive materials, and gasket materials.

The liner side adhesive is a different rubber-based adhesive that bonds well to most substrates at room temperature. This adhesive exhibits high initial tack and high peel strength.

Application:

- Excellent bond to urethane foams
- Die cuts cleanly

Technical Data

<i>Adhesive</i>		Rubber-Based
<i>Substrate</i>		Polyester Film
<i>Thickness (mils)</i>		3.5 (0.09 mm)
<i>Carrier</i>		0.5 mils (0.013 mm)
<i>Adhesion to Steel (oz/in of width)</i>	Liner Side	147 (40.19 N/25mm)
	Exposed Side	125 (34.18 N/25mm)
<i>Application Temperature</i>		68°F to 100°F (20°C to 37.8°C)
<i>Service Temperature</i>		30°F to 150°F (-1.1°C to 65.6°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.