



Product Information

CT 307 Double-Coated Polyester Film

Description:

A high tack, moderate shear acrylic adhesive film coated on both sides of a polyester film. This product exhibits all the positive results associated with a high quality general purpose acrylic system. With a 55# white, densified kraft liner; it has excellent resistance to oils, plasticizers, and UV light. Can withstand higher temperatures than rubber-based adhesive systems and exhibits resistance to some plasticizers. Adhesion is excellent to a very wide variety of substrates.

Application:

- For bonding and laminating to a variety of cloths, vinyls, corks, paper, rigid and flexible plastics.
- For mounting displays.
- Die cuts cleanly.
- Excellent peel and shear.

Technical Data

<i>Adhesive</i>		Acrylic
<i>Substrate</i>		Polyester Film
<i>Thickness (mils)</i>		3.5 (0.09 mm)
<i>Carrier</i>		0.5 mils (0.013 mm)
<i>Adhesion to Steel (oz/in of width)</i>	Liner Side	60 (16.4 N/25mm)
	Exposed Side	60 (16.4 N/25mm)
<i>Application Temperature</i>		68°F to 100°F (20°C to 37.8°C)
<i>Service Temperature</i>		-30°F to 220°F (-34°C to 104°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.