



## Product Information

### CT 309 Red Double-Coated Pressure Sensitive Adhesive

#### Description:

Polyester film, double-coated with a red high tack acrylic adhesive. Product is supplied on a 50# tan kraft release liner. Provides extremely high tack for flying splices and excellent adhesion in cold temperatures. Good shear and heat resistance and red color allows visual identification of splices. Polyester film carrier adds dimensional stability to composite.

#### Application:

- High-speed flying splice of papers, films, foils, and corrugated fiber board.
- General purpose bonding.
- Application of decorative parts.

#### Technical Data

Adhesive	Acrylic
Substrate	50# Kraft Paper
Thickness (mils)	3.5 (0.09 mm)
Carrier (PET)	0.5 (0.012 mm)
Adhesion to Steel (oz/in of width)	43 (12 N/25mm)
Application Temperature	65°F (18°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.