



Product Information

CT 310 Double-Coated Polyethylene Tape

Description:

Double-coated polyethylene film with permanent adhesive. Thin profile allows conformability and permanency. Used for general purpose double-coated applications. Excellent for carpet hold-down.

Application:

- General purpose double-coated applications.
- Carpet hold-down.

Technical Data

<i>Adhesive</i>	Permanent
<i>Substrate</i>	Polyethylene Film
<i>Thickness (mils)</i>	3 (0.076 mm)
<i>Adhesion to Steel (oz/in of width)</i>	50 (13.9 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	4 (17.9 N/25mm)
<i>Elongation (% at Break)</i>	100

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.