

Product Information

CT 313 Transparent UPVC Plate Mounting Tape

Description:

Double-coated UPVC plate mounting tape with a natural rubber adhesive. Unwind characteristics offer easier tape mounting. The structured polypropylene liner prevents the formation of air pockets when plate mounting. Plates are easily repositioned during mounting as the full adhesion of the tape only becomes effective during the print run.

The high adhesion and good shear resistance ensure that there is no plate movement or edge life problems, even at high speeds and on extended print runs. On demounting, there is no adhesive residue on the plate or cylinder. This product is especially appropriate to the mounting of photopolymer plates on compressible sleeves.

Application:

• For mounting of photopolymer plates in flexographic printing, especially on compressible sleeves.

Technical Data	
Adhesive	Natural Rubber
Substrate	PVC Film
Thickness (mils)	3.93 (0.1 mm)
Tensile Strength (Ibs/in of width)	22 (98.4 N/25mm)
Elongation (% at Break)	40

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602 Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.