



Product Information

CT 318 Double-Coated Crepe Paper Tape

Description:

Double-Coated crepe paper tape with a synthetic rubber adhesive. Great for applications requiring conformability and strength, it's used in the printing and corrugated industries for splicing operations. Exhibits high tack and high shear for permanent and semi-removable applications.

Application:

- Mounting rubber and plastic printing plates.
- Holding wood cuts and dies.
- Core start up and end-tabling.

Technical Data

<i>Adhesive</i>		Synthetic Rubber
<i>Substrate</i>		Crepe Paper
<i>Liner</i>		52# White Paper
<i>Thickness (mils)</i>		7.5 (0.19 mm)
<i>Adhesion to Steel (ozs/in of width)</i>		90 (24.6 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	MD	14 (62.6 N/25mm)
	CD	7 (31.3 N/25mm)
<i>Elongation (% at Break)</i>		12
<i>Service Temperature</i>		0°F to 180°F (-18°C to 82°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.