



Product Information

CT 333 Double-Coated Polyester Film

Description:

General purpose grade double-coated polyester film tape for mounting plastic parts, rubber profiles, and extruded parts and profiles, as well as for bonding electronic components. Good initial tack, excellent adhesion to a variety of surfaces and conformability to irregular surfaces.

Application:

- For mounting plastic parts, rubber profiles and extruded parts and profiles
- Can also be used for bonding electronic components

Technical Data

<i>Adhesive</i>	Solvent-Based Acrylic
<i>Substrate</i>	Polyester Film
<i>Liner</i>	Poly-coated Kraft
<i>Thickness (mils)</i>	3.5 (0.09 mm)
<i>Adhesion to Steel (oz/in of width)</i>	65 (7.1 N/10 mm)
<i>Elongation (% at break)</i>	100
<i>Tensile Strength (lbs/in)</i>	7.5 (13.1 N/ 10 mm)
<i>Service Temperature</i>	-4°F to 176°F (-20°C to 80°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.