



Product Information

CT 347 Double Coated Polyester Film Tape

Description:

Polyester film, double coated with a removable* acrylic PSA on the liner side and a high performance, permanent rubber adhesive on the exposed side. This product is supplied with a 60# release liner. The exposed side provides excellent adhesion to many surfaces, and the polyester film carrier adds dimensional strength and stability.

Application:

- Laminate to foams and felts for protective pads.
- Temporary labels and decals.
- Temporary protective packaging.

Technical Data

<i>Adhesive</i>	Rubber
<i>Liner</i>	Removable* Acrylic
<i>Substrate</i>	Polyester Film
<i>Liner</i>	60#
<i>Thickness (mils)</i>	2.55 (0.066 mm)
<i>Adhesion to Steel (oz/in of width)</i>	117 (32.5 N/25mm)
<i>Liner</i>	25 (7 N/25mm)
<i>Application Temperature</i>	65°F or Above (18°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

* Removability property does not apply to aluminium surfaces.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.