



Product Information

CT 364 Double-Coated High Strength Polyurethane Foam Tape

Description:

High strength polyurethane foam tape designed with an open-cell structure that allows air and moisture to reach the silicone for optimum curing of the silicone. Semi-rigid polyurethane foam is compatible with all silicone tested and low thermal conductivity improves the performance of the wall and can support LEED points. Available in different thicknesses.

Application:

- Glazing tape
- Bumper protection
- Low thermal conductivity

AAMA approved thermal barrier spacer

Technical Data

| | |
|------------------------------------|----------------------------------|
| Adhesive | Acrylic |
| Substrate | Polyurethane |
| Thickness | 3/8" |
| Adhesion to Steel (oz/in of width) | 45 (310 kPa) |
| Tensile Strength (lbs/in of width) | 130 (896 kPa) |
| Elongation (% at break) | 125 |
| Service Temperature | -40°F to 180°F (-40°C to 82.2°C) |
| Application Temperature | 60°F to 125°F (16°C to 52°C) |

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.