



## Product Information

### CT 366 Double-Coated High Strength Polyurethane Foam Tape

#### Description:

High strength polyurethane foam tape designed with an open-cell structure that allows air and moisture to reach the silicone for optimum curing of the silicone. Semi-rigid polyurethane foam is compatible with all silicone tested and low thermal conductivity improves the performance of the wall and can support LEED points. Available in different thicknesses.

#### Application:

- Glazing tape
- Bumper protection
- Low thermal conductivity

*AAMA approved thermal barrier spacer*

#### Technical Data

Adhesive	Acrylic
Substrate	Polyurethane
Thickness	1/4"
Adhesion to Steel (oz/in of width)	45 (310 kPa)
Tensile Strength (lbs/in of width)	130 (896 kPa)
Elongation (% at break)	125
Service Temperature	-40°F to 180°F (-40°C to 82.2°C)
Application Temperature	60°F to 125°F (16°C to 52°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.