



## Product Information

**CT 370**

**Double-Coated XLPE Foam Tape**

### Description:

1/32" thick, cross-linked white polyethylene foam tape with high tack and high shear with a synthetic rubber adhesive. Available in other thicknesses.

### Application:

- Mounting
- Nameplates/point-of-purchase displays
- Reflectors

### Technical Data

Adhesive	Synthetic Rubber
Substrate	Polyethylene
Thickness	1/32"
Adhesion to Steel (oz/in of width)	160 (43.75 N/25mm)
Service Temperature	30°F to 150°F (-1.1°C to 65.6°C)
Application Temperature	68°F to 100°F (20°C to 37.8°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.