



Product Information

CT 394

Double-Coated Tape with Fabric Backing

Description:

Double-coated tape with a white, flexible fabric backing; siliconized liner and rubber adhesive. High coating weight is well suited for mounting on irregular surfaces.

Application:

- Mounting on irregular surfaces
- Splicing textiles, synthetics and carpet installation

Technical Data

<i>Adhesive</i>	Rubber
<i>Substrate</i>	Fabric
<i>Thickness (mils)</i>	15.4 (0.391 mm)
<i>Adhesion to Steel (oz/in of width)</i>	68.5 (7.5 N/cm)
<i>Tensile Strength (lbs/in of width)</i>	45.7 (80 N/cm)
<i>Elongation (% at Break)</i>	10

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.