



Product Information

CT 402 General Purpose Grade Plastic Vinyl Electrical Tape

Description:

7 mil plastic vinyl electrical tape available in different colors. It is suitable for all weather conditions and is flame retardant. This tape also resists chemicals, acids, abrasions, corrosion, moisture and sunlight.

Application:

- Thin, tough and resilient tape used for quick identification and color coding
- Resists chemicals, acids, abrasion, corrosion, moisture and

Meets Spec: HH-I-595C; ASTM-D-3005; UL & CSA APPROVED

Technical Data	
Adhesive	Rubber
Substrate	Plastic Vinyl
Thickness (mils)	7 (0.178 mm)
Adhesion to Steel (oz/in of width)	23 (6.3 N/25mm)
Tensile Strength (lbs/in of width)	18 (80.5 N/25mm)
Elongation (% at Break)	200
Dielectric Strength (Volts)	8,750 (7,900 wet)
Insulation Resistance	1x10 ¹⁴ MΩ
Temperature Rating (UL)	176°F (80°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.