



Product Information

CT 404 Premium Grade Plastic Vinyl Electrical Tape

Description:

7 mil premium grade plastic vinyl electrical tape suitable for all weather. It is flame retardant.

Application:

- Quick identification and color coding
- Primary insulation up to 600 volts

Meets Spec: UL 510, CSA 22.2; ASTM-D-3005; HH-I-595C

Technical Data

Adhesive	Rubber
Substrate	Plastic Vinyl
Thickness (mils)	7 (0.178 mm)
Adhesion to Steel (oz/in of width)	20 (2.2 N/cm)
Tensile Strength (lbs/in of width)	17 (30 N/cm)
Elongation (% at Break)	260
Dielectric Strength (Volts)	9,000 (8,100 wet)
Insulation Resistance	1x10 ⁶ MΩ
Temperature Rating (UL)	14°F to 176°F (-10°C to 80°C)
Temperature Rating (CSA)	-0.4°F to 221°F (-18°C to 105°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.