

Product Information

CT 408

Premium Grade Vinyl Electrical Tape

Description:

7 mil premium grade, all weather, flame retardant PVC that resists extremely cold temperatures and suitable for all weather conditions. This high performance tape resists chemicals, acids, abrasion, corrosion, moisture and sunlight.

Application:

- High performance electrical applications requiring moisture-tight electrical and mechanical protection in exteme environments
- Resists chemicals, acids, abrasion, corrosion, moisture and sunlight

Meets Spec: UL 510; CSA approved

Technical Data	
Substrate	PVC
Thickness (mils)	7 (0.178 mm)
Adhesion to Steel (oz/in of width)	16 (4.4 N/25mm)
Tensile Strength (lbs/in of width)	18 (80.5 N/25mm)
Elongation (% at Break)	200
Dielectric Strength (Volts)	8,750
Temperature Rating (UL)	176°F (80°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.