



Product Information

CT 412

Abrasion Resistant Polyester Film Tape

Description:

2 mil polyester film with a thermosetting rubber adhesive that is non-corrosive. Resistant to abrasion and has a temperature performance up to 130°C. (Available in clear and yellow)

Application:

- Tough abrasion resistant tape used for a variety of electrical applications requiring temperature performance up to 130°C

Meets Specs: MIL-I-15126F, Type MFT

Technical Data

Adhesive	Thermosetting Rubber
Substrate	Polyester Film
Thickness (mils)	3.5 (0.09 mm)
Adhesion to Steel (oz/in of width)	45 (12.3 N/25mm)
Tensile Strength (lbs/in of width)	50 (219 N/25mm)
Elongation (% at Break)	100
Dielectric Strength (volts)	5,000
Temperature Rating	130°C

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.